## Decoded Class 1 - Intro & Accessibility

1) ICC A117.1 allows projections of up to 4" into the required clear opening width in what area of the opening height?
<ul> <li>a. between 36" and 48" above the floor</li> <li>b. between 34" and 48" above the floor</li> <li>c. between 34" and 80" above the floor</li> <li>d. between 30" and 80" above the floor</li> </ul>
2) To provide more clear opening width, what type of hinges could be used?
<ul><li>a. swing clear hinges</li><li>b. wide throw hinges</li><li>c. center pivots</li><li>d. continuous hinges</li></ul>
3) The maximum threshold height for a door on an accessible route is?
a. 1/4" b. 1/2" c. 3/4" d. 1"
4) Operating hardware on doors on an accessible route must be mounted in what portion of the door height?
<ul> <li>a. between 34" and 48" above the floor</li> <li>b. between 36" and 48" above the floor</li> <li>c. below 48" above the floor</li> <li>d. between 15" and 48" above the floor</li> </ul>
5) ICC A117.1 states that doors on an accessible route must close from 90 degrees to 12 degrees in how many seconds?
<ul><li>a. 3 seconds</li><li>b. 6 seconds</li><li>c. 4 seconds</li><li>d. 5 seconds</li></ul>

- 6) ICC A117.1 limits the maximum allowable opening force for interior swinging non-firerated doors to what amount of force?
  - a. 15 pounds
  - b. 8.5 pounds
  - c. 5 pounds
  - d. no stated requirement
- 7) ICC A117.1 limits the maximum allowable opening force for interior swinging fire doors to what amount?
  - a. 15 pounds
  - b. 8.5 pounds
  - c. 5 pounds
  - d. no stated requirement
- 8) ICC A117.1 prohibits projections in the bottom 10" on the push side of which doors?
  - a. all swinging doors
  - b. manual swinging doors
  - c. automatic swinging doors
  - d. swinging and sliding doors
- 9) When a vision lite is installed in a door on an accessible route, the bottom of the lite must be:
  - a. between 36" and 48" above the floor
  - b. a maximum of 42" above the floor
  - c. between 34" and 48" above the floor
  - d. a maximum of 43" above the floor
- 10) The allowable unobstructed forward reach range for a person in a wheelchair is defined by ICC A117.1 as:
  - a. between 15" and 48" above the floor
  - b. between 30" and 48" above the floor
  - c. between 34" and 48" above the floor
  - d. between 36" and 48" above the floor